

Search within category

GO

BUY NOW

DESIGN / INSTALL



QL1B1P3BN2491

Vertical switched power strip with per outlet power and environmental monitoring, 30 A, 208V, WYE, 18 IEC C-13 and 6 IEC C-19 locking receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, three 20 A double pole magnetic breaker/on-off switch with integral switch guard, and 10' power cord with NEMA L21-30P twist lock plug. UL and c-UL Listed. Dimensions: 72.0"H x 2.5"W x 2.3"D Breaker Doghouse add 1.44" (87.4) to overall depth (1829mm x 64mm x 57mm)

This part number has been obsoleted with no replacement. [Click here](#) to contact customer service for further assistance.

Specs	Packaging Details	Documents
OM Obsolete Code	OBSOLETE	
CE Compliant	No	
UL Listed	Yes	
Rack PDU Type	Monitored and Switched Per Outlet Rack PDU	
Monitoring	Monitored Per Outlet	
Remote Outlet Switching	Yes	
Mount Orientation	Vertical	
Current Rating (Amps)	30A	
Input Voltage	208V - Three Phase WYE	
Plug Type	NEMA L21-30P	
Output Voltage	208V	
Receptacle Type	IEC C-13 Locking and IEC C-19 Locking	
Total Number of Outlets	24	
Depth (In.)	2.25	
Depth (mm)	57.2	
Height (In.)	72.00	
Height (mm)	1828.8	
Width (In.)	2.50	
Width (mm)	63.5	
Tool-Less Button Spacing (In.)	64.75	
Tool-Less Button Spacing (mm)	1644.7	
No. of Rack Spaces	0	
Surge Suppression	No	
Color	Black	
Length (mm)	3000	
RoHS Compliancy Status	Compliant	
Min. Order Qty.	1	