

Search Results

- Evaluate
- FAQs
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Product On-Line Catalog > Search Results >

Current refinements (click ☐ to remove) Search Tips ☐

☐ Text Search: 'QL1B2G6BN2491'

Your search criteria matched only one product, shown below

QL1B2G6BN2491



- Remote switching capability for power cycling individual outlets or a group of outlets on or off to reboot equipment or power off individual outlets to stop unauthorized use
- Per outlet monitoring provides data to determine if power allocations are accurate and the efficiency metric of any server in the data center allowing individual servers to be identified as candidates for additional capacity, redeployment, or decommissioning
- Time delay sequencing avoids circuit overload due to high in-rush current at equipment start up
- Remote access to power consumption data via a web-based GUI provides global network access to real-time power information
- Integrates with Panduit® PIM™ Software which aggregates power information through a single web based GUI
- Measure in-cabinet temperature, humidity, airflow, and dew point remotely to prevent environmental factors that can cause equipment to overheat or malfunction
- Alarm messaging capability provides user-defined alarm/messaging capabilities for specific

events that exceeded thresholds

- Each outlet has a green LED for indication if the outlet is on or off for easy visual identification
- Optional remote LED display available for local monitoring, part number PVQ-RD

<input type="checkbox"/> Part Number	QL1B2G6BN2491
<input type="checkbox"/> RoHS Compliancy Status	Compliant
<input type="checkbox"/> Part Description	Vertical switched power strip with per outlet power and environmental monitoring, 60 A, 208V, Delta, 18 IEC C-13 and 6 IEC C-19 locking receptacles, red LED current monitor, RJ-45 Ethernet port with two RJ12 remote environmental ports, six 20 A double pole magnetic breaker/on-off switch with integral switch guard, and 10' power cord with IEC 60309 - 3P+E plug. UL and c-UL Listed. Dimensions: 66.0"H x 4.0"W x 3.4"D (1683mm x 102mm x 87mm)
<input type="checkbox"/> Product Type	Vertical Power Outlet Unit
<input type="checkbox"/> Color	Black
<input type="checkbox"/> Depth (In.)	3.4
<input type="checkbox"/> Depth (mm)	87
<input type="checkbox"/> Height (In.)	66.3
<input type="checkbox"/> Height (mm)	1683
<input type="checkbox"/> Width (In.)	4.0
<input type="checkbox"/> Width (mm)	102
<input type="checkbox"/> Plug Type	IEC 60309 - 3P + E
<input type="checkbox"/> Pricing Description	Vertical 60 AMP, 3 Phase WYE 208V Switched with Per Outlet Power and Environmental Monitoring
<input type="checkbox"/> Mn. Order UOM	PC
<input type="checkbox"/> Mn. Order Qty.	1
<input type="checkbox"/> Voltage	208V
<input type="checkbox"/> BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
<input type="checkbox"/> Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.