Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
- PDF-Switched POU ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor
Install & Maintain
- Installation Instructions
- PDF-Panduit POU..

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'QL1B2G6BN24R1'**

Your search criteria matched only one product, shown below

QL1B2G6BN24R1

• Remote switching capability for power cycling individual outlets or a group of outlets on or off to reboot equipment or power off individual outlets to stop unauthorized use
• Per outlet monitoring provides data to determine if power allocations are accurate and the efficiency metric of any server in the data center allowing individual servers to be identified as candidates for additional capacity, redeployment, or decommissioning
• Time delay sequencing avoids circuit overload due to high in -rush current at equipment start up
• Remote access to power consumption data via a web -based GUI provides global network access to real -time power information
• Integrates with Panduit ® PIM™ Software which aggregates power information through a single web based GUI
• Measure in -cabinet temperature, humidity, airflow, and dew point remotely to prevent environmental factors that can cause equipment to overheat or malfunction
• Alarm messaging capability provides user -defined alarm/messaging capabilities for specific events that exceeded thresholds
• Each outlet has a green LED for indication if the outlet is on or off for easy visual identification
• Optional remote LED display available for local monitoring, part number PVQ -RD
• Outlet Group Overload Protection allows user defined amperage threshold for a group of outlets to prevent accidental circuit breaker overload

Part Number	QL1B2G6BN24R1
RoHS Compliancy Status	Compliant
Part Description	Vertical switched power strip with per outlet power and environmental monitoring, 60 A, 208 V, Delta, 18 IEC C13 and 6 IEC C19 receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, six 20 A double pole magnetic breaker on-off switch with integral switch guard, and 10' power cord with IEC 60309 – 3P/4W, plug. UL and cUL Listed. Dimensions: 63"H x 4"W x 3.4"D (1683mm x 102mm x 87mm)
Product Type	Vertical Power Outlet Unit
Color	Black
CE Compliant	No
Plug Type	IEC 60309 3P/4W
Pricing Description	Vertical, Mixed (18) C-13 & (6) C-19, Switched with Per Outlet Power & Environmental Monitored 208V, 60A Three-Phase POU
Min. Order UOM	PC
Min. Order Qty.	1
Voltage	208V
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy