

Search within category

GO

BUY NOW

DESIGN / INSTALL



QL1D2P3BN2401

Vertical power strip 32 A, 230/400V, WYE, 21 IEC C-13 and 3 IEC C-19 locking receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, three 16 A double pole magnetic breaker/on-off switch with integral switch guard, and 3m power cord with IEC 60309 - 3P+N+E pin in sleeve connector. Complies with IEC 60950-1, EN 55022, EN 55024 and CE Marked. Dimensions: 66.3"H x 2.0"W x 2.25"D Breaker Doghouse add 1.44" (87.4) to overall depth (1683mm x 51mm x 58mm)

|                                |                                            |           |                    |              |
|--------------------------------|--------------------------------------------|-----------|--------------------|--------------|
| Specs                          | Packaging Details                          | Documents | ★ Add to Favorites | 🛒 Add to BOM |
| CE Compliant                   | Yes                                        |           |                    |              |
| UL Listed                      | No                                         |           |                    |              |
| Rack PDU Type                  | Monitored and Switched Per Outlet Rack PDU |           |                    |              |
| Monitoring                     | Monitored Per Outlet                       |           |                    |              |
| Remote Outlet Switching        | Yes                                        |           |                    |              |
| Mount Orientation              | Vertical                                   |           |                    |              |
| Current Rating (Amps)          | 32A                                        |           |                    |              |
| Input Voltage                  | 400V - Three Phase WYE                     |           |                    |              |
| Plug Type                      | IEC 60309 - 6H 3P+N+E Red Splashproof      |           |                    |              |
| Output Voltage                 | 230V                                       |           |                    |              |
| Receptacle Type                | IEC C-13 Locking and IEC C-19 Locking      |           |                    |              |
| Total Number of Outlets        | 24                                         |           |                    |              |
| Depth (In.)                    | 2.25                                       |           |                    |              |
| Depth (mm)                     | 57.2                                       |           |                    |              |
| Height (In.)                   | 72.00                                      |           |                    |              |
| Height (mm)                    | 1828.8                                     |           |                    |              |
| Width (In.)                    | 2.50                                       |           |                    |              |
| Width (mm)                     | 63.5                                       |           |                    |              |
| Tool-Less Button Spacing (In.) | 64.75                                      |           |                    |              |
| Tool-Less Button Spacing (mm)  | 1644.7                                     |           |                    |              |
| No. of Rack Spaces             | 0                                          |           |                    |              |
| Surge Suppression              | No                                         |           |                    |              |
| RoHS Compliancy Status         | Compliant                                  |           |                    |              |
| Min. Order Qty.                | 1.0000                                     |           |                    |              |