

Search within category

GO

BUY NOW

DESIGN / INSTALL



QN1A1C0BA24E1

Vertical power strip 20 A, 120V, 24 NEMA 5-20R receptacles, with red LED current monitor, RJ-45 Ethernet port with two RJ12 remote environmental ports, remote display port, and 10' power cord with NEMA 5-20P plug. UL and c-UL Listed. Dimensions: 66.3H x 2.0W x 2.0D (1683mm x 51mm x 51mm)

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
Rack PDU Type	Monitored Rack PDU			
Monitoring	Aggregate Power Monitoring			
Remote Outlet Switching	No			
Mount Orientation	Vertical			
Current Rating (Amps)	20A			
Input Voltage	120V - Single Phase			
Plug Type	NEMA 5-20P			
Output Voltage	120V			
Receptacle Type	NEMA 5-20R Duplex			
Total Number of Outlets	24			
Depth (In.)	2.25			
Depth (mm)	57.2			
Height (In.)	66.25			
Height (mm)	1682.8			
Width (In.)	2.00			
Width (mm)	50.8			
Tool-Less Button Spacing (In.)	64.75			
Tool-Less Button Spacing (mm)	1644.7			
No. of Rack Spaces	0			
Surge Suppression	No			
Amps	20A			
Application	Can either be utilized standalone for smaller installations or seamlessly feed information directly into the Physical Infrastructure Manager™ (PIM™) Software Platform for larger data centers.			
Length (In.)	71.50			
Part Features	Remote access to power consumption data, Integrates with Panduit® PIM™ Software, Environmental Monitoring, Alarm messaging capability and Integrated power monitoring and management.			
Standards	UL and c-UL Listed 60950			
UL Recognized	Yes			
Voltage	120V			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			

