

Search within category

GO

BUY NOW

DESIGN / INSTALL



QN1B1L2BN30P1

Vertical power strip 30 A, 208V, 24 IEC C-13 and 6 IEC C-19 receptacles, with red LED current monitor, RJ-45 Ethernet port with two RJ12 remote environmental ports, remote display port, two 20 A double pole magnetic breaker/on-off switch with integral switch guard, and 10' power cord with NEMA L6-30P twist lock plug. UL and c-UL Listed. Dimensions: 66.3"H x 2.0"W x 2.0"D Breaker Doghouse add 1.44" (87.4) to overall depth (1683mm x 51mm x 51mm)

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
UL Listed	Yes			
Rack PDU Type	Monitored Rack PDU			
Monitoring	Aggregate Power Monitoring			
Remote Outlet Switching	No			
Mount Orientation	Vertical			
Current Rating (Amps)	30A			
Input Voltage	208V - Single Phase			
Plug Type	NEMA L6-30P			
Output Voltage	208V			
Receptacle Type	IEC C-13 and IEC C-19			
Total Number of Outlets	30			
Depth (In.)	2.25			
Depth (mm)	57.2			
Height (In.)	66.25			
Height (mm)	1682.8			
Width (In.)	2.00			
Width (mm)	50.8			
Tool-Less Button Spacing (In.)	64.75			
Tool-Less Button Spacing (mm)	1644.7			
No. of Rack Spaces	0			
Surge Suppression	No			
Application	Can either be utilized standalone for smaller installations or seamlessly feed information directly into the Physical Infrastructure Manager™ (PIM™) Software Platform for larger data centers.			
Length (In.)	118.11			
Length (mm)	3000			
Part Features	Remote access to power consumption data, Integrates with Panduit® PIM™ Software, Environmental Monitoring, Alarm messaging capability and Certification/Agency approvals			
Standards	UL and c-UL Listed 60950			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			

