

Search within category

GO

BUY NOW

DESIGN / INSTALL



QS1B1L2BN24AA1

Vertical switched power strip 30 A, 208V, 20 IEC C-13 and 4 IEC C-19 locking receptacles, 10Mb RJ-45 Ethernet port with two RJ12 remote environmental ports, two 20 A double pole magnetic breaker on-off switch with integral switch guard, and 10' power cord with NEMA L6-30P twist lock plug. UL and c-UL Listed. Dimensions: 70.0"H x 2.5"W x 2.3"D Breaker Doghouse add 1.44" (87.4mm) to overall depth (1683mm x 64mm x 57mm).

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
UL Listed	Yes			
Rack PDU Type	Monitored and Switched Rack PDU			
Monitoring	Aggregate Power Monitoring			
Remote Outlet Switching	Yes			
Mount Orientation	Vertical			
Current Rating (Amps)	30A			
Input Voltage	208V - Single Phase			
Plug Type	NEMA L6-30P			
Output Voltage	208V			
Receptacle Type	IEC C-13 Locking and IEC C-19 Locking			
Total Number of Outlets	24			
Depth (In.)	2.25			
Depth (mm)	57.2			
Height (In.)	70.00			
Height (mm)	1778.0			
Width (In.)	2.50			
Width (mm)	63.5			
Tool-Less Button Spacing (In.)	64.75			
Tool-Less Button Spacing (mm)	1644.7			
Surge Suppression	No			
Color	Black			
Length (mm)	3000			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			