

Search Results

- Evaluate
- FAQs
- Design a Solution
- Part Drawings
 - PDF-Switched and ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Product On-Line Catalog > Search Results >

Current refinements (click ☐ to remove) Search Tips ☐

☐ Text Search: 'QS1B2G6BN2491'

Your search criteria matched only one product, shown below

QS1B2G6BN2491



- Remote switching capability for power cycling individual outlets or a group of outlets on or off to reboot equipment or power off individual outlets to stop unauthorized use
- Time delay sequencing avoids circuit overload due to high in-rush current at equipment start up
- Remote access to power consumption data via a web-based GUI provides global network access to real-time power information
- Integrates with Panduit® PIM™ Software which aggregates power information through a single web based GUI
- Measure in-cabinet temperature, humidity, airflow and dew point remotely to prevent environmental factors that can cause equipment to overheat or malfunction
- Alarm messaging capability provides user-defined alarm/messaging capabilities for specific events that exceeded thresholds
- Each outlet has a green LED for indication if the outlet is on or off for easy visual identification

☐ Part Number	QS1B2G6BN2491
☐ RoHS Compliancy Status	Compliant
☐ Part Description	Vertical switched power strip 60 A, 208V, Delta, 18 IEC C-13 and 6 IEC C-19 locking receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, red LED current monitor, remote display port, six 20 A double pole magnetic breaker on-off switch with integral switch guard, and 10' power cord with IEC 60309 - 3P+ N+ E, 60A pin in sleeve connector. UL and c-UL Listed. Dimensions: 66.3"H x 4.0"W x 3.4"D (1683mm x 102mm x 87mm)
☐ Product Type	Vertical Power Outlet Unit
☐ Color	Black
☐ Depth (in.)	3.4
☐ Depth (mm)	87
☐ Height (in.)	66.3
☐ Height (mm)	1683
☐ Width (in.)	4.0
☐ Width (mm)	102
☐ Plug Type	IEC 60309 - 3P+ N+ E
☐ Pricing Description	Vertical POU, 60 Amp x 3 Phase DELTA, (18) C-13 and (6) C-19 IEC 60309 - 3 pole/4 wire, 60A, Pin in Sleeve Connector, Watertight
☐ Mn. Order UOM	PC
☐ Mn. Order Qty.	1
☐ Voltage	208V
☐ BOM Qty. (# of Pkgs.)	0
☐ Add to Favorite Product List	☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.