

Search within category

GO

BUY NOW

DESIGN / INSTALL



QS1B2T6BN2491

Vertical switched power strip, 50 A, 208V, WYE, 18 IEC C-13 and 6 IEC C-19 locking receptacles, red LED current monitor, RJ-45 Ethernet port with two RJ12 remote environmental ports, three 20 A double pole magnetic breaker on-off switch with integral switch guard, and 10' power cord with California Style 50 Amp twist lock plug. UL and c-UL Listed. Dimensions: 66.0"H x 4.0"W x 3.4"D (1683mm x 102mm x 87mm)

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
UL Listed	Yes			
Rack PDU Type	Monitored and Switched Rack PDU			
Monitoring	Aggregate Power Monitoring			
Remote Outlet Switching	Yes			
Mount Orientation	Vertical			
Current Rating (Amps)	50A			
Input Voltage	208V - Three Phase Delta			
Plug Type	CS-8365C			
Output Voltage	208V			
Receptacle Type	IEC C-13 Locking and IEC C-19 Locking			
Total Number of Outlets	24			
Depth (In.)	3.44			
Depth (mm)	87.4			
Height (In.)	66.25			
Height (mm)	1682.8			
Width (In.)	4.00			
Width (mm)	101.6			
Tool-Less Button Spacing (In.)	64.75			
Tool-Less Button Spacing (mm)	1644.7			
No. of Rack Spaces	0			
Surge Suppression	No			
Color	Black			
Length (mm)	3000			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			