

Search within category

GO

BUY NOW

DESIGN / INSTALL



QS1D2Q0BA2401

Vertical switched power strip16 A, 230/400V, WYE, 21 IEC C-13 and 3 IEC C-19 locking receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports and 3mm power cord with IEC 60309 - 3P+ N+ E, 16A pin in sleeve connector. Complies with IEC 60950-1, EN 55022, EN 55024 and CE Marked. Dimensions: 66.3"H x 2.5"W x 2.3"D (1683mm x 64mm x 57mm)

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
CE Compliant	Yes			
UL Listed	No			
Rack PDU Type	Monitored and Switched Rack PDU			
Monitoring	Aggregate Power Monitoring			
Remote Outlet Switching	Yes			
Mount Orientation	Vertical			
Current Rating (Amps)	16A			
Input Voltage	400V - Three Phase WYE			
Plug Type	IEC 60309 - 6H 3P+N+E Red Splashproof			
Output Voltage	230V			
Receptacle Type	IEC C-13 Locking and IEC C-19 Locking			
Total Number of Outlets	24			
Depth (In.)	2.25			
Depth (mm)	57.2			
Height (In.)	66.25			
Height (mm)	1682.8			
Width (In.)	2.50			
Width (mm)	63.5			
Tool-Less Button Spacing (In.)	64.75			
Tool-Less Button Spacing (mm)	1644.7			
No. of Rack Spaces	0			
Surge Suppression	No			
Color	Black			
Length (mm)	3000			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			