

Search within category

GO

BUY NOW

DESIGN / INSTALL

QZ1A1M2CM10E1



Horizontal auto transfer switch 30 A, 120V, 10 NEMA 5-20R receptacles, two LEDs power-on indicators with RJ-45 Ethernet port, red LED current monitor, two 20 A single pole magnetic breaker on-off switch with integral switch guard, and dual 10' power cord with NEMA L5-30P twist lock plugs. UL and c-UL Listed. Power Feeds A and B must be Phase Synchronized. Dimensions: 1.72"H x 17.0"W x 9.0"D (44mm x 431mm x 229mm)

This part number has been obsoleted with no replacement. [Click here](#) to contact customer service for further assistance.

Specs

Packaging Details

Documents

OM Obsolete Code	OBSOLETE
CE Compliant	No
UL Listed	Yes
Rack PDU Type	Auto Transfer Switch Rack PDU
Monitoring	Aggregate Current Monitoring
Remote Outlet Switching	No
Mount Orientation	Vertical
Current Rating (Amps)	30A
Input Voltage	120V - Single Phase
Plug Type	(2) NEMA L5-30P
Output Voltage	120V
Receptacle Type	NEMA 5-20R Duplex
Total Number of Outlets	10
Depth (In.)	8.00
Depth (mm)	203.2
Height (In.)	1.72
Height (mm)	43.7
Width (In.)	17.12
Width (mm)	434.8
Tool-Less Button Spacing (In.)	None
Tool-Less Button Spacing (mm)	None
No. of Rack Spaces	0
Surge Suppression	No
Application	Single-power corded equipment.
BMEcat - Type of Connection	Connecting cord with plug
Cable Length	3
Color	Black
ETIM Number	EC002762
Keywords	Power outlet unit
Length (mm)	3000
Part Features	Scrolling power meter, Switching and Dual input power sources

Standards	UL and c-UL Listed to 60950
Sub Brand	Auto Transfer Switch
RoHS Compliancy Status	Compliant
Min. Order Qty.	1
