

NOTES:
1. IDENTIFICATION: VERTICAL, (24) 5-20R
120V / 20A / 3-PHASE WYE POU

2. ACCESSORY COMPONENTS:
 (4) #10-32 x 1/2" MOUNTING SCREWS
 (4) #12-24 x 1/2" MOUNTING SCREWS
 (2) #10-32 LOCKING COLLAR SCREWS
 (2) L-BRACKETS

4. UL® & c-UL® LISTED 60950 AND NOM COMPLIANT.

6. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.

8. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.

66.25 (1682.8)

WHITE

PANDUIT P/N	WEIGHT
VB0A1J0BA24E1	13 lb (5.9 kg)

Diagram of a square column cross-section. The overall width and height are both labeled as 2.0 (50.8). The section contains four reinforcement bars, represented by '+' symbols, arranged in a square pattern within the core. Arrows indicate the dimensions for the overall size and the spacing of the reinforcement.



01A	9-5-12	PIP	MRWA	A. UPDATED NOTE #4 & 7. B. ADDED NOTE #8.	09V098CP				
00A	2-24-11	MAV	KRKE	RELEASED TO PRODUCTION	09V098CP				
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH	

MODEL FILENAME			09V098CP/01.PRT		
CAD FILENAME/LAYERS			09V098CP_DC/01A.PRT		
PANDUIT			CORP TINLEY PARK, ILLINOIS		
VERTICAL, (24) 5-20R POWER OUTLET UNIT CUSTOMER DRAWING					
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:			UNLESS OTHERWISE SPECIFIED,		
INCHES X.X +/- 0.03 X.XX +/- 0.015 X.XXX +/- 0.005			[METRIC - MILLIMETER] X. +/- 0.8 X.X +/- 0.4 X.XX +/- 0.13		
			ANGLE +/- 1°		
DRAWN BY MAV			SCALE NONE		
DATE 2-24-11			DRAWING NO. 09V098CP		DWG B
CHK'D KRKE					