

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable

1434965
<https://www.phoenixcontact.com/us/products/1434965>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-pos., PUR halogen-free, RAL 7021 black-gray, straight M12 SPEEDCON plug, to valve connector A, with 1 LED, connected to varistor, cable length: 0.5 m

Commercial data

Item number	1434965
Packing unit	1 pc
Minimum order quantity	25 pc
Note	Made to order (non-returnable)
Sales key	BF07
Product key	BF1DJA
GTIN	4046356691024
Weight per piece (including packing)	49.7 g
Weight per piece (excluding packing)	49.7 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable



1434965

<https://www.phoenixcontact.com/us/products/1434965>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	TPU
Material housing valve plug	PBT
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Contact material	CuSn
Valve plug contact insert material	PBT
Contact surface material	Ag

Electrical properties

Insulation resistance	$\geq 10 \text{ M}\Omega$
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	4 A

Signaling

Status display	1 LED
Status display present	Yes

Connector

Connection 1

Type	Plug straight M12 SPEEDCON
Number of positions	3
Locking type	SPEEDCON
Coding type	A
Material	CuSn (Contact)
	Ni/Au (Contact surface)
	TPU GF (Contact carriers)

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable



1434965

<https://www.phoenixcontact.com/us/products/1434965>

	TPU, hardly inflammable, self-extinguishing (Grip body)
--	---


Connection 2

Type	Valve connector A
Material	CuSn (Contact)
	Ag (Contact surface)
	PBT (Contact carriers)
	PBT (Housing)

Cable/line

Cable length	0.5 m
--------------	-------

PUR halogen-free black [PUR]

Dimensional drawing	
Cable weight	30 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	3x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm (Signal line)
External cable diameter	4.50 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	min. 20 MΩ*km
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	22.5 mm
Smallest bending radius, movable installation	45 mm

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable



1434965

<https://www.phoenixcontact.com/us/products/1434965>

Max. bending cycles	15000000
Bending radius	50 mm
Traversing path	0.9 m
Traversing rate	5 m/s
Acceleration	30 m/s ²
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	according to DIN VDE 0482
	According to DIN EN 50265-2-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	largely oil-resistant
	partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-20 °C ... 85 °C (valve plug)
	-30 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 70 °C (Cable, flexible installation)

Standards and regulations

Standard designation	Valve connector
Standards/specifications	EN 175301-803

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable




1434965

<https://www.phoenixcontact.com/us/products/1434965>

Drawings

Schematic diagram




Pin assignment M12 plug, 3-pos., valve connector

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable

1434965


<https://www.phoenixcontact.com/us/products/1434965>

Dimensional drawing



Valve connector, type A

Schematic diagram



Valve connector pin assignment, type A


SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable



1434965

<https://www.phoenixcontact.com/us/products/1434965>

Dimensional drawing



Plug, M12 x 1, straight, shielded

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable



1434965
<https://www.phoenixcontact.com/us/products/1434965>

Classifications

ECLASS

ECLASS-11.0	27060312
ECLASS-13.0	27060312

SAC-3P-MS/0,5-PUR/A-1L-V3/4SCO - Sensor/actuator cable



1434965

<https://www.phoenixcontact.com/us/products/1434965>

Accessories

SAC-V-SCREW-M3-29 KNURL - Screw

1403779

<https://www.phoenixcontact.com/us/products/1403779>

Fillister head screw with plastic knurl, M3 x 40



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com