

SACC-VB-3CON-M16/BI-1L-SV 24V - Valve connectors



1452233
<https://www.phoenixcontact.com/us/products/1452233>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Valve connectors, Universal, 3-position, Valve connector BI (11 mm), Screw connection, cable gland M16, external cable diameter 6 mm ... 8 mm

Commercial data

Item number	1452233
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF36
Product key	BF2DCA
Catalog page	Page 30 (C-2-2019)
GTIN	4046356536400
Weight per piece (including packing)	24.86 g
Weight per piece (excluding packing)	25.5 g
Customs tariff number	85366990
Country of origin	HU

SACC-VB-3CON-M16/BI-1L-SV 24V - Valve connectors



1452233

<https://www.phoenixcontact.com/us/products/1452233>

Technical data

Notes

Assembly note

NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Product properties

Product type	Valve connectors
Sensor type	Universal
Number of positions	3
No. of cable outlets	1
Shielded	no
Pg screw connection	M16

Data management status

Article revision	03
------------------	----

Insulation characteristics


Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material housing valve plug	PA
Contact material	CuZn
Contact surface material	CuSn

Dimensions

Dimensional drawing



Width	21 mm
Height	33.2 mm
Length	40.5 mm

External dimensions

Outside diameter	6 mm ... 8 mm
------------------	---------------

Electrical properties

Contact resistance	$\leq 4 \text{ m}\Omega$
--------------------	--------------------------

SACC-VB-3CON-M16/BI-1L-SV 24V - Valve connectors



1452233

<https://www.phoenixcontact.com/us/products/1452233>

Insulation resistance	> 2 GΩ
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	1.5 A
Protective circuit	Surge protection; Varistor

Valve connector characteristics

Fixing screws	M3 x 33,5
---------------	-----------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	50 (Valve connector)
-----------------------------	----------------------

Signaling

Status display	LED (yellow)
Status display present	Yes

Connection data

Connection method	Screw connection
Conductor cross section	0.25 mm ² ... 1.5 mm ²
Connection cross section AWG	24 ... 16
Tightening torque	1.8 Nm ±0.2 Nm (Pressure screw)
	0.4 Nm ±0.1 Nm (Central screw)
	0.2 Nm ±0.1 Nm (Contact screw)

Connector

Connection 1

Head design	Valve connector
Head thread type	BI (11 mm)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-25 °C ... 60 °C (valve plug)


SACC-VB-3CON-M16/BI-1L-SV 24V - Valve connectors

1452233


<https://www.phoenixcontact.com/us/products/1452233>

Drawings

Dimensional drawing



Circuit diagram



SACC-VB-3CON-M16/BI-1L-SV 24V - Valve connectors



1452233
<https://www.phoenixcontact.com/us/products/1452233>

Classifications

ECLASS

ECLASS-11.0	27440105
ECLASS-12.0	27440105
ECLASS-13.0	27440105

ETIM

ETIM 9.0	EC003623
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

1452233
<https://www.phoenixcontact.com/us/products/1452233>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-25
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	ef772dfe-ea69-43c7-82f2-3be3bbb9c554

SACC-VB-3CON-M16/BI-1L-SV 24V - Valve connectors



1452233

<https://www.phoenixcontact.com/us/products/1452233>

Accessories

SAC-3P-100,0-PUR/0,5 - Cable reel

1457393

<https://www.phoenixcontact.com/us/products/1457393>



By the meter, Cable reel, PUR halogen-free, black-gray RAL 7021, 3-wire, color single wire: black 1, black 2, green/yellow, cable length: 100 m

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com