

# SACB-4/ 4-C - Distributor box



1692857

<https://www.phoenixcontact.com/us/products/1692857>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, connection method: M12 socket Plastic, number of slots: 4, number of positions: 4, coding: A, slot assignment: single, status display: No, Universal; master cable connection: Pluggable screw connection 180°, shielding: no

## Your advantages

- Safety in the field, thanks to robust housing and high degree of protection
- Flexible: distributor box with connector hood for on-site assembly

## Commercial data

Item number	1692857
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	BF3CBD
Catalog page	Page 115 (PC-2009)
GTIN	4017918178048
Weight per piece (including packing)	157.5 g
Weight per piece (excluding packing)	111.5 g
Customs tariff number	85444290
Country of origin	PL

# SACB-4/ 4-C - Distributor box



1692857

<https://www.phoenixcontact.com/us/products/1692857>

## Technical data

### Product properties

Product type	Distributor box
Number of positions	4
Number of slots	4
Coding	A
LED	no

### Electrical properties

Max. operating voltage $U_{\max}$	135 V
Nominal voltage $U_N$	120 V
Rated current, total	10 A
	2x 8 A (For electrical isolation)
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

### Connection data

#### Conductor connection

Sensor/actuator connection system	M12 socket
Conductor cross section Flexible signal line	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section Flexible power supply	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Connection cross section AWG Flexible signal line	26 ... 16
Connection cross section AWG Flexible power supply	26 ... 16
Stripping length Signal line	7 mm
Tightening torque slot sensor/actuator cable	0.4 Nm
Tightening torque, union nut	2.5 Nm

#### Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = 1 / 4
	2 / 4 (A) = 2 / 4
	3 / 4 (A) = 3 / 4
	4 / 4 (A) = 4 / 4
	1-4 / 1 (+ 24 V) = $U_N$
	1-4 / 3 (0 V) = 0 V
	1-4 / 5 (PE) = PE

### Signaling

Status display present	No
------------------------	----

### Dimensions

# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



Dimensional drawing	
Width	54 mm
Height	41 mm
Length	116.5 mm

## Material specifications

Material Threaded sleeve	PA
Material Housing	PA
Flammability rating according to UL 94	V0
Seal material O-ring	NBR
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA 6.6 V0
Material of contact surface, master cable side	Sn

## Cable/line

External cable diameter	7 mm ... 12 mm
Connection method	Pluggable screw connection

## Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 75 °C

# SACB-4/ 4-C - Distributor box




1692857

<https://www.phoenixcontact.com/us/products/1692857>

## Drawings

Circuit diagram




# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



Dimensional drawing




# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>

Schematic diagram



Electrically isolated. Potential assignment:  $U_{N1}$  = slots 1,3 and  $U_{N2}$  = slots 2,4.


# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



Schematic diagram



Potential  $U_{N1}$  and  $U_{N2}$  bridged. Potential assignment:  $U_{N1} = U_{N2} = \text{slots } 1,2,3,4$ .


# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



Schematic diagram



M12 slot, socket, 4-pos.



# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



## Classifications

### ECLASS

ECLASS-11.0	27440111
ECLASS-13.0	27440111

# SACB-4/ 4-C - Distributor box



1692857

<https://www.phoenixcontact.com/us/products/1692857>

## Accessories

### SACB-C-H180 8/16 - Connector hood

1695977

<https://www.phoenixcontact.com/us/products/1695977>



Connector hood with integrated connector, for M12 sensor/actuator boxes with plastic thread and plug-in screw connection, for 4, 6 or 8 slots

---

### PROT-M12 - Screw plug

1680539

<https://www.phoenixcontact.com/us/products/1680539>



An M12 screw plug for the unoccupied M12 sockets of the sensor/actuator cable, boxes and flush-type connectors

## SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



## ZBN 18:UNBEDRUCKT - Zack marker strip

2809128

<https://www.phoenixcontact.com/us/products/2809128>



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

---

## SACB- 4X0,34/ 3X0,75-50,0 PUR - Master cable ring

1503328

<https://www.phoenixcontact.com/us/products/1503328>



Master cable for sensor/actuator boxes, with PE conductor, unshielded, material PUR/PVC, 7-pos., 4 x 0.34 mm<sup>2</sup> and 3 x 0.75 mm<sup>2</sup>

# SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



## TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

---

## SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

## SACB-4/ 4-C - Distributor box

1692857

<https://www.phoenixcontact.com/us/products/1692857>



## SACC BIT M12-D20 - Tool

1208445

<https://www.phoenixcontact.com/us/products/1208445>

Nut for assembling M12 connectors for assembly with a knurl diameter of 20 mm, for 4 mm hexagonal drive



---

## SZK PZ2 VDE - Screwdriver

1206463

<https://www.phoenixcontact.com/us/products/1206463>

Screwdriver, PZ crosshead, VDE insulated, size: PZ 2 x 100 mm, 2-component grip, with non-slip grip



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)