

2880341

<https://www.phoenixcontact.com/us/products/2880341>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Surge voltage protection combination type 2 for 690 V AC in a TN-C system



Commercial data

Item number	2880341
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	CL1222
Catalog page	Page 47 (TT-2011)
GTIN	4046356048811
Weight per piece (including packing)	404.4 g
Weight per piece (excluding packing)	404.4 g
Customs tariff number	85363030
Country of origin	DE

SYS-SET/3/T2/690 - Type 2 surge protection device



2880341

<https://www.phoenixcontact.com/us/products/2880341>

Technical data

Product properties

Product type	Surge arrester
IEC test classification	II
	T2
EN type	T2
IEC power supply system	TN-C
	IT
Type	DIN rail module, two-section, divisible
Surge protection fault message	Optical, remote indicator contact

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal frequency f_N	50 Hz (60 Hz)
Nominal voltage U_N	400 V AC (690 V AC)
	500 V AC (3/PE-IT)

Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	Changeover contact
Maximum operating voltage U_{max} AC	250 V AC
Maximum operating voltage U_{max} DC	125 V DC
Max. operating current I_{max}	1 A AC (ohmic)
	200 mA DC (ohmic)
	1 A AC (inductive)
	30 mA DC (inductive)

Connection data

Connection method	Screw terminal block
Screw thread	M5
Tightening torque, min	4.5 Nm
Stripping length	14.5 mm
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	25 mm ²
Conductor cross section, rigid min.	0.5 mm ²
Conductor cross section, rigid max.	35 mm ²

Remote fault indicator contact

Connection method	Screw connection
Screw thread	M2
Tightening torque, min	0.25 Nm

SYS-SET/3/T2/690 - Type 2 surge protection device




2880341

<https://www.phoenixcontact.com/us/products/2880341>

Stripping length	7 mm
Conductor cross section flexible min.	1.5 mm ²
Conductor cross section flexible max.	0.14 mm ²
Conductor cross section, rigid min.	1.5 mm ²
Conductor cross section, rigid max.	0.14 mm ²

Dimensions

Dimensional drawing	
Width	53 mm
Height	102.8 mm
Depth	65.5 mm
Horizontal pitch	3 Div.

Material specifications

Flammability rating according to UL 94	V0
Housing material	PA

Protective circuit

Direction of action	3L-PEN 3L-PE
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	600 V AC
Maximum continuous operating voltage U_C (L-PEN)	600 V AC
Residual current I_{PE}	≤ 0.25 mA
Standby power consumption P_C	≤ 600 mVA
Nominal discharge current I_n (8/20) μ s (L-PEN)	15 kA 45 kA (all channels)
Maximum discharge current I_{max} (8/20) μ s (L-PEN)	30 kA
Voltage protection level U_p (L-PEN)	≤ 2.7 kV
Response time t_A (L-PEN)	≤ 25 ns
Total surge current (8/20) μ s	45 kA
Max. backup fuse with branch wiring	125 A (gL/gG)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C

SYS-SET/3/T2/690 - Type 2 surge protection device



2880341

<https://www.phoenixcontact.com/us/products/2880341>

Standards and regulations

Air clearances and creepage distances

Standards/regulations	IEC 60664-1 / DIN VDE 0110-1
-----------------------	------------------------------

Standards


Standards/regulations	IEC 61643-1
	DIN EN 61643-11
	DIN EN 61643-11/A11
Standards/specifications	IEC 61643-1
Note	2005
Standards/specifications	DIN EN 61643-11
Note	2002
Standards/specifications	DIN EN 61643-11/A11
Note	2007

Mounting


Mounting type	DIN rail: 35 mm
---------------	-----------------

Drawings

Dimensional drawing



Circuit diagram



SYS-SET/3/T2/690 - Type 2 surge protection device



2880341

<https://www.phoenixcontact.com/us/products/2880341>

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com