

2901665

https://www.phoenixcontact.com/us/products/2901665

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail power supply unit 24 V DC/20 A, primary switched-mode, 1-phase. The SFB technology (Selective Fuse Breaking Technology) can now also be used to trigger standard power circuit breakers reliably and quickly.

Product description

QUINT POWER power supply units – Superior system availability with SFB technology
Compact power supply units of the new QUINT POWER generation maximize the availability of your system. With the SFB technology (Selective
Fuse Breaking Technology), six times the nominal current for 12 ms, even the standard power circuit-breakers can now also be triggered reliably
and quickly. Faulty current paths are switched off selectively, the fault is located and important system parts continue to operate. Comprehensive
diagnostics are provided through constant monitoring of output voltage and current. This preventive function monitoring visualizes critical operating
modes and reports them to the control unit before an error can occur.

Commercial data

Item number	2901665
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	NULL
Product key	CMPQ13
GTIN	4046356623933
Weight per piece (including packing)	3,400 g
Weight per piece (excluding packing)	3,400 g
Customs tariff number	85044095
Country of origin	TH



2901665

https://www.phoenixcontact.com/us/products/2901665

Technical data

_				
Ρ	rodi	ICT.	nroi	perties

	Product type	Power supply	
Mounting			
	With protective coating	No	
Material specifications			
	Housing material	Metal	



2901665

https://www.phoenixcontact.com/us/products/2901665

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27040390	
	ECLASS-12.0	27040390	
	ECLASS-13.0	27040390	
ETIM			
	ETIM 9.0	EC002498	
UNSPSC			
UNSPSC			

32121700



2901665

https://www.phoenixcontact.com/us/products/2901665

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes	
Exemption	6(c), 7(a), 7(c)-l	
EU REACH SVHC		
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)	



2901665

https://www.phoenixcontact.com/us/products/2901665

Accessories

UWA 182/52 - Mounting adapter

2938235

https://www.phoenixcontact.com/us/products/2938235



Universal wall adapter for securely mounting the device in the event of strong vibrations. The device is screwed directly onto the mounting surface. The universal wall adapter is attached on the top/bottom.

ME-MAX-NEF/QUINT20A - EMC filter

2319919

https://www.phoenixcontact.com/us/products/2319919



Filter for adherence to the EMC category EMC1 in shipbuilding for the QUINT-PS/1AC/24DC/20 power supply



2901665

https://www.phoenixcontact.com/us/products/2901665

QUINT-PS/FAN/4 - Fan

2320076

https://www.phoenixcontact.com/us/products/2320076



The fan for QUINT-PS/1AC and .../3AC can be mounted without the need for tools or other accessories. By using the fan, optimum cooling is ensured at high ambient temperatures or if the mounting position is rotated.

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com