


3 & 5 WATT REGULATED DC/DC CONVERTERS

KEY FEATURES

- Recommended For Highspeed Analog Applications
- Input/Output Isolated
- PC Mountable
- Continuous Short Circuit Protection, Self Recovering
- Line Regulation: 0.02%
- Load Regulation: 0.02%
- Single & Dual Outputs
- Pi Input Filter
- No Derating To 71°C
- Wide Input Range
- High Power Density
- Designed To Meet FCC SEC 15, Sub-part J, A and B
- 100% Burned-In
- 3 Year Warranty



DESCRIPTION

The A and D Series of DC/DC converters provide tight regulation and accuracy in a compact, cost effective package. The series operates from nominal inputs of 5, 12 or 24VDC with single and dual output voltages. Outputs feature extremely low noise. The series provides 3 to 6 watts of output with high efficiency. Designed for board level applications such as A/D and D/A converters, operational and instrument amplifiers, and portable data acquisition equipment.

SELECTION GUIDE Standard Products

DEVICE TYPE	INPUT VOLTAGE RANGE VDC	NL CURRENT A (MAX)	FL INPUT CURRENT A (MAX)	OUTPUT VOLTAGE VDC	OUTPUT CURRENT ma (MAX)	PACKAGE/ PINOUT
3A5RN5	4.5 - 5.5	.300	1.20	+or-5	600	A
3D5RN5	4.5 - 5.5	.300	1.20	+or-5	600	D
3A5RN12-12	4.5 - 5.5	.200	1.60	±12	±150	A
3D5RN12-12	4.5 - 5.5	.200	1.60	±12	±150	D
3A5RN15-15	4.5 - 5.5	.200	1.90	±15	±150	A
3D5RN15-15	4.5 - 5.5	.200	1.90	±15	±150	D
5D5RN5	4.5 - 5.5	.300	1.82	+or-5	1000	D
5A5RN12-12	4.5 - 5.5	.300	2.40	±12	±250	A
5D5RN12-12	4.5 - 5.5	.300	2.40	±12	±250	D
5A5RN15-15	4.5 - 5.5	.300	2.40	±15	±200	A
5D5RN15-15	4.5 - 5.5	.300	2.40	±15	±200	D
5A12RN5	10.8 - 13.2	.050	.72	+or-5	1000	A
5A12RN12-12	10.8 - 13.2	.100	.85	±12	±250	A
5A12RN15-15	10.8 - 13.2	.100	.85	±15	±250	A
5A24RN5	21.6 - 26.4	.050	.35	+or-5	1000	A
5D24RN5	21.6 - 26.4	.050	.35	+or-5	1000	D
5A24RN12-12	21.6 - 26.4	.050	.45	±12	±250	A
5A24RN15-15	21.6 - 26.4	.050	.45	±15	±200	A




GENERAL ELECTRICAL SPECIFICATIONS

(Specifications at Nominal Input and 25°C)

PARAMETER	LIMIT	CONDITIONS
Input Filter	Pi Filter	All Device Types
Input/Output Isolation		
Voltage	500 VDC (Min.)	All Units
Resistance	10 ³ megohms (Min)	
Output Voltage Accuracy	± 1%	Factory Set
Load Regulation	0.02% (Max.)	NL to FL ±12V and ±15V
		Output Models
	0.1% (Max.)	5V Output Models
Line Regulation	0.02% (Max.)	Low Line to High Line
		at Full Load
Output Voltage Stability	0.02%/°C	Typical
Output Noise/Ripple	40mV P-P (Max.)	20Hz - 20MHz Bandwidth
Short Circuit Protection	Current Limited	All Units
Duration	Continuous	
Thermal Overload	Dual Output Units	
Protection		
Foldback Current Limiting	Single Output Units	
Switching Frequency	25 KHz	
Operating Temperature	-25°C to +71°C	
Derating	None	To 71°C
Storage Temperature	-35°C to +125°C	

MECHANICAL SPECIFICATIONS



PIN	SINGLE OUTPUT	DUAL OUTPUT
1	+INPUT	+INPUT
2	-INPUT	-INPUT
3	+OUTPUT	+OUTPUT
4	COMMON	COMMON
5	COMMON	-OUTPUT

NOTES:

- ALL DIMENSIONS IN PARENTHESES ARE METRIC.
- TOLERANCES UNLESS OTHERWISE SPECIFIED: .XX = ±.03 (.76)
.XXX = ±.015 (.38)

Reliability Incorporated
P.O. Box 218370
Houston, TX 77218
TEL: (713) 492-0550
FAX: (713) 492-0615

East Coast Sales Office
P.O. Box 157
Dunstable, MA 01827
TEL: (508) 937-4055
FAX: (508) 649-9319

Reliability Singapore Pte. Ltd.
5004 Ang Mo Kio
Avenue 5, #04-01
Singapore 2056
TEL: 65-481-9266
FAX: 65-481-2612

RICR de Costa Rica S.A.
P.O. Box 1-3006
Zone Franca Metropolitana
Barreal, Heredia
Costa Rica, A.C.
TEL: 506-293-4384
FAX: 506-293-4621

European Sales Office
P.O. Box 87
Newbury
Berkshire, RG14 6YT
England
TEL: 44-635-522298
FAX: 44-635-580870

Copyright© 1994, Reliability Incorporated.
Reliability reserves the right to make
changes in the product at any time, without
notification.
12-64-12M-694

These products are not authorized for use as critical components in life support devices or systems without the express written approval of an officer of Reliability Incorporated.

7652818 0000161 T17