

SAMLEX POWER PRODUCTS

FEATURES

Short circuit and over voltage protection
Output power rated at continuous service
Binding post output terminals
Precision regulation of output voltage
Low peak-peak ripple
External fuse access
High surge capacity

APPLICATIONS

Cellular telephones
Auto-sound display and mobile sound systems
Testing of DC equipment and appliances
Household and portable entertainment equipment
Automobile accessories
Security systems
Toys and hobbies
Cooler boxes



RPS Series Power Supplies



3 Amps / 7 Amps

TECHNICAL SPECIFICATIONS

Model	RPS-1203	RPS-1207
Input Voltage Range	110 - 120 VAC, 60 Hz	110 - 120 VAC, 60 Hz
Output Voltage	13.8 VDC	13.8 VDC
Output Current		
Continuous	3 A	7 A
Maximum Surge	5 A	10 A
Output Voltage Stability	+/- 0.05 V	+/- 0.05 V
Fuse Rating	1 A	2 A
Peak to Peak Ripple	< 10 mV	< 10 mV
Operating Temperature	0° C to 40° C	
Protections		
	Short Circuit	Short Circuit
	Over Voltage	Over Voltage
Enclosure	Heavy duty metal cabinet	Heavy duty table top cabinet
Terminals	Binding post output terminals	
Dimensions (L x W x H)	7.3" x 5.1" x 3.5"	9.1" x 5.8" x 3.9"
Weight	5.0 lbs	8.5 lbs

Technical Specifications subject to change without notification.