

> You are here > Home > Products > UPS DI BAT I/O ISO 10-30KVA 48/60V SM

Share:

f

UPS DI BAT I/O ISO 10-30KVA 48/60V SM

0S-G3KDOCOPT011

Be the first to [write a review](#)

UPS DI BAT I/O ISO 10-30KVA 48/60V SM

Not available in United States, call for more information

Product Support

?

Product FAQs

✓

Product Registration

Product Overview	Ratings & Reviews
MGE Galaxy 3000 Features & Benefits	
Serviceability	
Multiple levels of service	With the option of packages or individual service components, our services are structured to allow you to pick and choose what you would like APC to do for you.
Front-access servicing	Simplifies installation and UPS maintenance while minimizing space requirements.
7x24 telephone technical support	Our experienced technical support engineers are available to answer your questions, giving you peace of mind knowing the help you need is there when you need it.
Availability	
Automatic internal bypass	Supplies utility power to the connected loads in the event of a UPS power overload or fault.
SmartSlot	Customize UPS capabilities with management cards.
Parallel-redundant capable	Power the connected equipment with multiple uninterruptible power supplies to increase system redundancy
Dual mains input	Increases availability by allowing the UPS to be connected to two separate power sources.
Network manageable	Provides remote power management of the UPS over the network.
Total Cost of Ownership	
Input power factor correction	Minimizes installation costs by enabling the use of smaller generators and cabling.
Fully-rated power kVA equals kW	Reduces cost by eliminating the need for an oversized UPS for Power Factor Corrected (PFC) loads.

WHO WE ARE

[About APC](#)

[Investor Relations](#)

[Careers](#)

[Sustainability](#)

CONNECT WITH US

[Press](#)

[APC Blog](#)

[Schneider Electric Data Center Blog](#)

[Contact Us](#)

[Rate this website](#)

FIND A RESELLER

FIND

CATALOG KEYCODE

GO

