Product data sheet

Specifications

APC

Rack PDU, Basic, 0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19

AP6120A

Overview

Lead Time	Usually in Stock

Main

Main Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Main Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Input Connection Type	IEC 60320 C20
Number Of Rack Unit	1U
Provided Equipment	Installation guide Safety guide

Physical

Height	4.4 cm
Width	38.8 cm
Depth	9.3 cm
Net Weight	1.56 kg
Mounting Location	Front Rear
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Usb Compatible	No

Input

[In] Rated Current	16 A
Permissible Voltage	100…240 V
Max Line Current	20 A
Input Current Limits	20 A
Load Capacity	2300 VA
Network Frequency	50/60 Hz

Output

Number Of Power Socket Outlets	7 IEC 60320 C13 2 IEC 60320 C19

Conformance

Product Certifications	cUL listed CE EAC IRAM PSE UL listed VDE

Packing Units

Package 1 Height	21 cm
Package 1 Width	43.6 cm
Package 1 Length	7.6 cm
Package 1 Weight	2.02 kg
Number Of Units In Package 3	100
Scc14	50731304327856

Contractual warranty

Warranty	2 years repair or replace

Sustainability

Green Premium™ label label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.
Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Energy Efficient   Take-back   RoHS/REACh

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Eu Rohs Directive   Compliant

EU RoHS Declaration