

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 30A, 100V, (24) 5-15

AP7532J

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	100 V 120 V
PDU type	Basic
Main Output Voltage	100 V
Input Connection Type	NEMA L5-30P
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Physical

Colour	Black
Height	161.9 cm
Width	5.6 cm
Depth	4.4 cm
Net weight	5.58 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
USB compatible	No
Mounting position	Vertical

Input

Input current limits	30 A
Load capacity	3000 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets24 NEMA 5-15R

Conformance

Product certificationsMETI Denan

Environmental

Ambient air temperature for operation-5...45 °C

Relative humidity5...95 %

Operating altitude0...15000 ft

Ambient air temperature for storage-25...65 °C

Storage Relative Humidity5...95 %

Storage altitude0.00...15240.00 m

Packing Units

Unit Type of Package 1PCE

Number of Units in Package 11

Package 1 Height213.4 cm

Package 1 Width12.7 cm

Package 1 Length15.2 cm

Package 1 Weight6.48 kg

Offer Sustainability

Sustainable offer statusGreen Premium product

REACH Regulation[REACH Declaration](#)

EU RoHS DirectiveCompliant
[EU RoHS Declaration](#)

Lead freeYes

Environmental Disclosure[Product Environmental Profile](#)

Circularity Profile[End of Life Information](#)

Optimized Energy EfficiencyEnergy efficient product

Take-backTake-back program available

Contractual warranty

Warranty2 years repair or replace

Recommended replacement(s)