

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 5.7kW, 120V, (42)5-20

AP7562

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	208 V 3 phases
PDU type	Basic
Main Output Voltage	120 V
Input Connection Type	NEMA L21-20P
Number of rack unit	0U
Cable length	0.91 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Physical

Colour	Black
Height	177.8 cm
Width	5.6 cm
Depth	4.4 cm
Net weight	5.45 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

Input

[In] rated current	16 A
Input current limits	20 A
Load capacity	5700 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets42 NEMA 5-20R

Conformance

Product certifications	cUL listed UL listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	6.36 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty2 years repair or replace

Recommended replacement(s)