

Product data sheet

Specifications

Rack PDU Extender, Basic, 2U, 30A, 120V, (12)5-20



AP7582

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	200 V 208 V
PDU type	Basic
Main Output Voltage	120 V
Input Connection Type	NEMA L14-30P
Number of rack unit	2U
Cable length	8.53 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

Physical

Colour	Black
Height	8.9 cm
Width	43.7 cm
Depth	8.9 cm
Net weight	6.36 kg
Mounting location	Front Rear
Mounting preference	Lower
Mounting mode	Rack-mounted
Mounting position	Horizontal

Input

[In] rated current	24 A
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets12 NEMA 5-20R

Conformance

Product certificationscUL listed
UL listed

StandardsCSA C22.2 No 107.1
UL 1778

Environmental

Ambient air temperature for operation0...45 °C

Relative humidity0...95 %

Operating altitude0...10000 ft

Ambient air temperature for storage-25...65 °C

Storage Relative Humidity0...95 %

Storage altitude0.00...15240.00 m

Packing Units

Unit Type of Package 1PCE

Number of Units in Package 11

Package 1 Height15.2 cm

Package 1 Width52.1 cm

Package 1 Length52.1 cm

Package 1 Weight7.27 kg

Offer Sustainability

Sustainable offer statusGreen Premium product

REACH Regulation[REACH Declaration](#)

EU RoHS DirectiveCompliant
[EU RoHS Declaration](#)

Lead freeYes

Environmental Disclosure[Product Environmental Profile](#)

Circularity Profile[End of Life Information](#)

Optimized Energy EfficiencyEnergy efficient product

Take-backTake-back program available

Contractual warranty

Warranty2 years repair or replace

Recommended replacement(s)