

# Product data sheet

Specifications



## Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32



AP7586

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	200 V 208 V 230 V
PDU type	Basic
Main Output Voltage	230 V
Number of rack unit	2U
Cable length	8.53 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

### Physical

Colour	Black
Height	8.9 cm
Width	43.7 cm
Depth	8.9 cm
Net weight	4.1 kg
Mounting location	Front Rear
Mounting preference	Lower
Mounting mode	Rack-mounted
Mounting position	Horizontal

### Input

Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire

Output

Number of power socket outlets4 IEC 60309

Conformance

Product certificationsCE  
VDE

Environmental

Ambient air temperature for operation0...45 °C

Relative humidity0...95 %

Operating altitude0...10000 ft

Ambient air temperature for storage-25...65 °C

Storage Relative Humidity0...95 %

Storage altitude0.00...15240.00 m

Packing Units

Unit Type of Package 1PCE

Number of Units in Package 11

Package 1 Height15.2 cm

Package 1 Width52.1 cm

Package 1 Length52.1 cm

Package 1 Weight4.99 kg

Offer Sustainability

Sustainable offer statusGreen Premium product

REACH Regulation[REACH Declaration](#)

EU RoHS DirectiveCompliant  
[EU RoHS Declaration](#)

Lead freeYes

Environmental Disclosure[Product Environmental Profile](#)

Circularity Profile[End of Life Information](#)

WEEEThe product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Optimized Energy EfficiencyEnergy efficient product

Take-backTake-back program available

Contractual warranty

Warranty2 years repair or replace

Recommended replacement(s)