

# Product data sheet

Specifications



## Rack PDU,Metered,ZeroU,5.7kW, 120&208V,(21)5-20&(6)L6-20

AP7602

⚠ Discontinued on: Jun 14, 2022

⚠ Discontinued

### Overview

Lead time Usually in Stock

### Main

Colour Beige

product or component type PDU

PDU type Metered

Cord length 0.9 m

Number of cables 1

### Complementary

Input Voltage 208 V 3 phases

Height 152.4 cm

Width 8.9 cm

Output Voltage 120 V  
208 V

Depth 4.4 cm

net weight 7.73 kg

Mounting preference No preference

Input Plug Type NEMA L21-20P

mounting mode Rack-mounted with kit

Rack units 0U

Mounting position Vertical

Permissible voltage 90...253 V

Input current limits 16 A

Load capacity 5700 VA

Number of power socket outlets 27

Network frequency 50/60 Hz

Outlet type and quantity 21 NEMA 5-20R  
6 NEMA L6-20R

### Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	cUL listed DOC/Industry Canada UL listed VCCI
Standards	FCC part 15 class A UL 1950
Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	0...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	182.9 cm
Package 1 Width	12.7 cm
Package 1 Length	10.2 cm
Package 1 Weight	8.622 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------