

# Product data sheet

Specifications



## Rack ATS, 208V, 30A, (2) L6-30P in, (1) L6-30R Out

AP7731

- !

Discontinued on: 23 August 2021
- !

End-of-service on: 30 October 2021

! Discontinued

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	200 V 208 V 230 V
Input Connection Type	NEMA L6-30P
Number of rack unit	2U
Cable length	2.44 m
Number of cables	2
Provided equipment	Documentation CD Installation guide Rack mounting brackets RS-232 configuration cable

### Physical

Colour	Black
Height	8.8 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	6.5 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

### Input

Network frequency	50/60 Hz
[In] rated current	24 A
Permissible voltage	200...240 V
Max line current	30 A
Input current limits	30 A

Output

Max current draw	30 A
Number of power socket outlets	1 NEMA L6-30R

Conformance

Product certifications	TÜV-C TÜV-NURTL VCCI class A
Standards	FCC part 15 class A ICES-003

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)

AP7731 is replaced by:

1x



APC Netshelter Rack Automatic Transfer Switch, 2U, 30A, 208V, 2 L6-30P IN, 1 L6-30R OUT, 50/60Hz  
AP4431A