

Product data sheet

Specifications

Rack PDU, Metered, 1U, 15A, 100/120V, (8) 5-15



AP7800

⚠ Discontinued on: Jun 30, 2021

⚠ End-of-service on: Jun 28, 2023

⚠ Discontinued

Overview

Lead Time Usually in Stock

Main

| | |
|-----------------------|--|
| Main Input Voltage | 100 V 120 V |
| Pdu Type | Metered |
| Main Output Voltage | 120 V |
| Input Connection Type | NEMA 5-15P |
| Number Of Rack Unit | 1U |
| Cable Length | 3.66 m |
| Number Of Cables | 1 |
| Provided Equipment | Cord retention bracket(s) Installation guide Rack mounting brackets User manual |

Physical

| | |
|---------------------|---------------|
| Height | 4.4 cm |
| Width | 44.4 cm |
| Depth | 10.2 cm |
| Net Weight | 1.73 kg |
| Mounting Location | Front Rear |
| Mounting Preference | No preference |
| Mounting Mode | Rack-mounted |
| Mounting Position | Horizontal |

Input

| | |
|----------------------|----------|
| [In] Rated Current | 12 A |
| Max Line Current | 1440 A |
| Input Current Limits | 15 A |
| Network Frequency | 50/60 Hz |

Output

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|--------------------------------|--------------|
| Number Of Power Socket Outlets | 8 NEMA 5-15R |
|--------------------------------|--------------|

Conformance

| | |
|------------------------|--|
| Product Certifications | cUL listed CSA METI Denan UL listed VCCI |
| Standards | FCC part 15 class A ICES-003 UL 60950 |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient Air Temperature For Operation | -5...45 °C |
| Relative Humidity | 5...95 % |
| Operating Altitude | 0...10000 ft |
| Ambient Air Temperature For Storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage Altitude | 0.00...15240.00 m |

Packing Units

| | |
|------------------------------|---------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.4 cm |
| Package 1 Width | 33.7 cm |
| Package 1 Length | 47 cm |
| Package 1 Weight | 2.91 kg |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)