

Product data sheet

Specifications



Rack PDU, Metered, 1U, 20A, 120V, (8) 5-20



AP7801B

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	100 V 120 V
PDU type	Metered
Main Output Voltage	120 V
Input Connection Type	NEMA L5-20P
Number of rack unit	1U
Cable length	3.66 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual

Physical

Height	4.4 cm
Width	44.4 cm
Depth	10.2 cm
Net weight	1.73 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

Input

[In] rated current	16 A
Input current limits	20 A
Load capacity	1920 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	8 NEMA 5-20R
--------------------------------	--------------

Conformance

Product certifications	cUL listed CSA UL listed
Standards	FCC part 15 class A ICES-003 UL 60950

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	33.7 cm
Package 1 Length	47 cm
Package 1 Weight	2.91 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)