

Product data sheet

Specifications



Rack PDU, Metered, Zero U, 20A, 100V, (24)5-15

AP7830J

❗ Discontinued on: 16 December 2020

❗ End-of-service on: 09 November 2022

❗ Discontinued

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	100 V 120 V
PDU type	Metered
Main Output Voltage	100 V
Input Connection Type	NEMA L5-20P
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit User manual

Physical

Colour	Black
Height	161.9 cm
Width	5.6 cm
Depth	4.4 cm
Net weight	4.86 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
USB compatible	No
Mounting position	Vertical

Input

Input current limits	20 A
Load capacity	2000 VA

Network frequency	50/60 Hz
-------------------	----------

Output

Number of power socket outlets	24 NEMA 5-15R
--------------------------------	---------------

Conformance

Product certifications	Industry Canada METI Denan VCCI
Standards	FCC part 15 class A ICES-003

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	5...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	5.78 kg

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)

AP7830J is replaced by:

1x



Rack PDU 2G, Metered, ZeroU, 20A, 100-120V, (24) 5-20R, Japan
AP8830J