# Product data sheet Characteristics

# AP7850B

Rack PDU, Metered, Zero U, 10A, 230V, (16) C13





# Overview

#### Main

| Color              | Black  |  |
|--------------------|--|--|
| PDU Type           | Metered  |  |
| Cable length       | 10 Ft (3.05 m)   |  |
| Number of cables   | 1  |  |
| Provided Equipment | Cord retention bracket(s)<br>Installation guide<br>Rack Mounting brackets<br>Toolless Mounting Kit |  |

| Complementary                  |                         |
|--------------------------------|-------------------------|
| Main Input Voltage             | 200 V<br>208 V<br>230 V |
| Height                         | 49.02 ln (124.5 cm)     |
| Width                          | 2.20 ln (5.6 cm)        |
| Output voltage                 | 230 V                   |
| Depth                          | 1.73 ln (4.4 cm)        |
| Net Weight                     | 6.77 Lb(US) (3.07 kg)   |
| Mounting Location              | Side                    |
| Mounting preference            | No preference           |
| Input Connection Type          | IEC 60320 C14           |
| Mounting Mode                  | Rack-mounted            |
| Number of rack unit            | 0U                      |
| Mounting position              | Vertical                |
| Acceptable Input Voltage       | 200250 V                |
| Max line current               | 10 A                    |
| Load Capacity                  | 2300 VA                 |
| Input Frequency                | 4763 Hz                 |
| Number of power socket outlets | 16 IEC 60320 C13        |
|                                |                         |

### Environment

| Product Certifications                | CE[RETURN]GOST[RETURN]VDE  |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | 23113 °F (-545 °C)         |
| Relative Humidity                     | 595 %                      |
| Operating altitude                    | 010000 ft                  |
| Ambient Air Temperature for Storage   | -13149 °F (-2565 °C)       |
| Storage Relative Humidity             | 595 %                      |
| Storage altitude                      | 050000 Ft (0.0015240.00 m) |

## Ordering and shipping details

| GTIN | 731304331537 |
|------|--------------|

# Packing Units

| Unit Type of Package 1       | PCE                   |  |
|------------------------------|-----------------------|--|
| Number of Units in Package 1 | 1                     |  |
| Package 1 Height             | 84.02 ln (213.4 cm)   |  |
| Package 1 Width              | 12.72 ln (32.3 cm)    |  |
| Package 1 Length             | 15.24 ln (38.7 cm)    |  |
| Package 1 Weight             | 8.77 Lb(US) (3.98 kg) |  |

# Offer Sustainability

| Sustainable offer status    | Green Premium product  |  |
|-----------------------------|--|--|
| California proposition 65   | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |  |
| REACh Regulation            | REACh Declaration  |  |
| EU RoHS Directive           | Compliant with Exemptions  |  |
| Lead free                   | Yes  |  |
| Mercury free                | Yes  |  |
| RoHS exemption information  | ₫Yes   |  |
| Environmental Disclosure    | Product Environmental Profile  |  |
| Circularity Profile         | ☑ End Of Life Information  |  |
| Optimized Energy Efficiency | Energy efficient product   |  |
| Take-back                   | Take-back program available  |  |

### Contractual warranty

| Warranty | 2 years repair or replace |
|----------|---------------------------|
|          |                           |

| Product Life Status : | Commercialised |  |
|-----------------------|----------------|--|
|-----------------------|----------------|--|

