

# Product data sheet

Specifications



## RackPDU,Metered,ZeroU,16A, 230V,(20)C13 &(4)C19, IEC C20

AP7852

⚠ Discontinued on: Jun 14, 2022

⚠ Discontinued

### Overview

Lead Time While Supplies Last

### Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C20
Number Of Rack Unit	0U
Cable Length	3.05 m
Number Of Cables	1
Provided Equipment	Installation guide Rack mounting brackets Toolless mounting kit User manual

### Physical

Colour	Black
Height	161.9 cm
Width	5.6 cm
Depth	4.4 cm
Net Weight	4.32 kg
Mounting Location	Side
Mounting Preference	No preference
Mounting Mode	Rack-mounted

### Input

Input Current Limits	16 A
Load Capacity	3680 VA
Network Frequency	50/60 Hz

### Output

Number Of Power Socket Outlets	20 IEC 60320 C13 4 IEC 60320 C19
--------------------------------	-------------------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Conformance

Product Certifications	CE GOST IRAM VDE
------------------------	---------------------------

## Environmental

Ambient Air Temperature For Operation	0...45 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m

## Packing Units

Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	7.74 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------