

Product data sheet

Specifications



Rack PDU, Metered, Zero U, 5.7kW, 120V, (42)5-20

AP7862

⚠ Discontinued on: 14 June 2022

⚠ Discontinued

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	208 V 3 phases
PDU type	Metered
Main Output Voltage	120 V
Input Connection Type	NEMA L21-20P
Number of rack unit	0U
Cable length	0.91 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit User manual

Physical

Colour	Black
Height	177.8 cm
Width	5.6 cm
Depth	4.4 cm
Net weight	5.46 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

Input

[In] rated current	16 A
Input current limits	20 A
Load capacity	5700 VA

Network frequency	50/60 Hz
-------------------	----------

Output

Number of power socket outlets	42 NEMA 5-20R
--------------------------------	---------------

Conformance

Product certifications	cUL listed cUL recognized UL listed
Standards	CSA C22.2 No 42 CSA C22.2 No. 60950-1-03 FCC part 15 class A UL 60950-1

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	8.841 kg

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)

AP7862 is replaced by:

1x



Rack PDU 2G, Metered, ZeroU, 20A, 120/208V 3Ph, (36) 5-20R
AP8862