

# Product data sheet

## Characteristics

# AP7863

Rack PDU, Metered, Zero U, 5.7kW, 120&208V, (21)5-20&(6)L6-20



## Commercial status

This Product is Obsolete : JUN 14, 2022

⚠ This Product is Obsolete

## Overview

Lead time	Usually in Stock
-----------	------------------

## Main

Color	Black
Product or Component Type	PDU
PDU Type	Metered
Cable length	3 Ft (0.9 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit User Manual

## Complementary

Main Input Voltage	208 V 3 phase
Height	70.0000000000 In (177.8 cm)
Width	2.2 In (5.6 cm)
Output voltage	120 V 208 V
Depth	1.7 In (4.4 cm)
Net Weight	12.02 Lb(US) (5.45 kg)
Mounting location	Side
Mounting preference	No preference
Input Connection Type	NEMA L21-20P
Mounting Mode	Rack-mounted
Number of rack unit	0U
Mounting position	Vertical
Line Rated Current	16 A
Input current limits	20 A
Load Capacity	5700 VA

Input Frequency	50/60 Hz
Number of power socket outlets	21 NEMA 5-20R 6 NEMA L6-20R

## Environment

Product Certifications	cUL Listed[RETURN]Industry Canada[RETURN]UL Listed
Standards	CSA C22.2 No. 60950-1-03 FCC Part 15 class A ICES-003 UL 60950-1
Ambient Air Temperature for Operation	32.0000000000...113.0000000000 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13.0000000000...149.0000000000 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 Ft (0.0000000000...15240.0000000000 m)




## Ordering and shipping details

GTIN	731304214281
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 In (213.4 cm)
Package 1 Width	6.0 In (15.2 cm)
Package 1 Length	5.0000000000 In (12.7 cm)
Package 1 Weight	19.491 Lb(US) (8.841 kg)

## Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **End of commercialisation**

## AP7863 may be replaced by any of the following products:



AP8863

Rack PDU 2G, Metered, ZeroU, 20A, 120/208V 3Ph, (24) 5-20R (6) L6-20R

Qty 1

Substitution date: |