

Product data sheet

Specifications



Rack PDU,Metered,ZeroU,14.4kW,208V, (24)C13,(4)C19,(2)L6-30R;10 CORD

AP7899B

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	208 V 3 phases
PDU type	Metered
Main Output Voltage	208 V
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Documentation CD Installation guide Rack mounting brackets RS-232 configuration cable Toolless mounting kit

Physical

Colour	Black
Height	177.8 cm
Width	5.6 cm
Depth	9.5 cm
Net weight	10.36 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

Input

[In] rated current	40 A
Input current limits	50 A
Load capacity	14400 VA
Network frequency	50/60 Hz

Number of input connectors	1 CS8365
----------------------------	----------

Output

Number of power socket outlets	2 NEMA L6-30R 24 IEC 60320 C13 4 IEC 60320 C19
--------------------------------	--

Conformance

Product certifications	cUL listed CSA Industry Canada METI Denan UL listed
Standards	FCC part 15 class A ICES-003 UL 60950

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	205.7 cm
Package 1 Width	7.9 cm
Package 1 Length	31.1 cm
Package 1 Weight	14.32 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)