

Product data sheet

Characteristics

AP7941

Rack PDU, Switched, Zero U, 30A, 200/208V,
(21)C13 & (3)C19



Commercial status

This Product is Obsolete : JUN 14, 2022

⚠ This Product is Obsolete

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Color	Black
PDU Type	Switched
Cable length	10 Ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit User Manual

Complementary

Main Input Voltage	200 V 208 V 230 V
Height	70.00 In (177.8 cm)
Width	2.20 In (5.6 cm)
Output voltage	200 V 208 V 230 V 240 V
Depth	1.73 In (4.4 cm)
Net Weight	16.29 Lb(US) (7.39 kg)
Mounting Location	Rear
Mounting preference	No preference
Input Connection Type	NEMA L6-30P
Mounting Mode	Rack-mounted
Number of rack unit	0U
Mounting position	Vertical
Line Rated Current	24 A

Acceptable Input Voltage	200...240 V
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19

Environment

Product Certifications	cUL Listed[RETURN]CCEE[RETURN]CSA[RETURN]Industry Canada[RETURN]METI Denan[RETURN]PSE[RETURN]UL Listed[RETURN]VCCI
Standards	FCC Part 15 class A ICES-003 UL 60950
Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 Ft (0.00...15240.00 m)




Ordering and shipping details

GTIN	731304225539
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 In (213.4 cm)
Package 1 Width	5.98 In (15.2 cm)
Package 1 Length	5.00 In (12.7 cm)
Package 1 Weight	18.26 Lb(US) (8.283 kg)

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **End of commercialisation**

AP7941 may be replaced by any of the following products:



APDU9941
APC Rack PDU, 9000 switched, 0U, 30A, 200V and 208V, 21 C13 and C15, 3 C19 and C21 sockets
Qty 1
Substitution date: |
