

Product data sheet

Specifications



Rack PDU, Switched, Zero U, 10A, 230V, (16) C13

AP7950B

Overview

Lead Time Usually in Stock

Main

Colour	Black
Product Or Component Type	PDU
Pdu Type	Switched
Cord Length	3.05 m
Number Of Cables	1
Provided Equipment	Cord retention bracket(s) Installation guide Rack mounting brackets Toolless mounting kit User manual

Complementary

Input Voltage	200 V 208 V 230 V
Height	124.5 cm
Width	5.6 cm
Output Voltage	230 V
Depth	4.4 cm
Net Weight	4.32 kg
Mounting Location	Rear
Mounting Preference	No preference
Input Plug Type	IEC 60320 C14
Mounting Mode	Rack-mounted
Rack Units	0U
Mounting Position	Vertical
Permissible Voltage	200...240 V
Max Line Current	10 A
Input Current Limits	10 A
Load Capacity	2300 VA
Network Frequency	47...63 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet Type And Quantity	16 IEC 60320 C13
--------------------------	------------------

Environment

Product Certifications	CE GOST IRAM VDE
------------------------	---------------------------

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
-----------	--

Ambient Air Temperature For Operation	-5...45 °C
---------------------------------------	------------

Relative Humidity	5...95 %
-------------------	----------

Operating Altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature For Storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage Altitude	0.00...15240.00 m
------------------	-------------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	213.4 cm
------------------	----------

Package 1 Width	12.7 cm
-----------------	---------

Package 1 Length	15.2 cm
------------------	---------

Package 1 Weight	5.23 kg
------------------	---------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
