Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Rack PDU, Switched, Zero U,16A, 230V,(21)C13&(3)C19, IEC309, 10' Cord

AP7954

! Discontinued on: Jun 10, 2022



Overview

Lead time Usually in Stock

Main

Mani		
Colour	Black	
PDU type	Switched	
Cord length	3.05 m	
Number of cables	1	
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets Toolless mounting kit User manual	

Complementary

•		
Input Voltage	200 V	
	208 V	
	230 V	
	250 V	
Height	161.9 cm	
Width	5.6 cm	
Output Voltage	230 V	
- ·		
Depth	4.4 cm	
net weight	5.92 kg	
mounting location	Rear	
		
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 2P + E	
mounting mode	Rack-mounted	
Rack units	OU	
Mounting position	Vertical	
Permissible voltage	220240 V	
Input current limits	16 A	
Load capacity	3680 VA	
Network frequency	4763 Hz	
Outlet type and quantity	21 IEC 60320 C13	
	3 IEC 60320 C19	
	2 IEC 00320 C13	

Life Is On Schneider Jun 30, 2024

Environment

Product certifications	CE
	VDE
Standards	EN 55022 class A
	EN 55024
	EN 61000-3-2
	EN 61000-3-3
	2.1.0.1000 0 0
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	6.806 kg

Contractual warranty

Warranty 2 years repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Energy Efficient Take-back Transparency

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Environmental Disclosure

Product Environmental Profile

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

End of Life Information