Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Rack PDU, Switched, Zero U, 12.5kW,208V,(21)C13&(3)C19,3' Cord

AP7968

! Discontinued on: Jun 10, 2022



Overview

Lead time Usually in Stock

Main

| Mairi | |
|---------------------------|---|
| Colour | Black |
| product or component type | PDU |
| PDU type | Switched |
| Cord length | 0.9 m |
| Number of cables | 1 |
| Provided equipment | Cord retention bracket(s) Documentation CD Installation guide Rack mounting brackets RS-232 configuration cable Toolless mounting kit |

Complementary

| Input Voltage | 208 V 3 phases |
|----------------------------------|----------------------|
| Height | 177.8 cm |
| Width | 5.6 cm |
| Output Voltage | 208 V |
| Depth | 8.9 cm |
| net weight | 8.08 kg |
| mounting location | Side |
| Mounting preference | No preference |
| mounting mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Max line current | 35 A |
| Input current limits | 35 A |
| | |
| Load capacity | 12500 VA |
| Load capacity Network frequency | 12500 VA 50/60 Hz |

| Outlet type and quantity | 21 IEC 60320 C13 |
|--------------------------|------------------|
| | 3 IEC 60320 C19 |

Environment

| Product certifications | cUL listed CSA Industry Canada UL listed |
|---------------------------------------|---|
| Standards | FCC part 15 class A ICES-003 UL 60950 |
| Ambient air temperature for operation | -545 °C |
| Relative humidity | 595 % |
| Operating altitude | 010000 ft |
| Ambient air temperature for storage | -2565 °C |
| Storage Relative Humidity | 595 % |
| Storage altitude | 0.000000000015240.000000000 m |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 210.8 cm |
| Package 1 Width | 15.2 cm |
| Package 1 Length | 12.7 cm |
| Package 1 Weight | 11.017 kg |

Contractual warranty

Warranty 2 years repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Energy Efficient Take-back Transparency

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information