

Product data sheet

Specifications



Rack PDU 2G, Switched, ZeroU, 20A, 100-120V, (24) 5-20R

AP8930

Overview

Presentation	APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Lead Time	Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Input Connection Type	NEMA L5-20P
Number Of Rack Unit	0U
Cable Length	3.00 m
Number Of Cables	1
Provided Equipment	Installation guide Rack mounting brackets Serial configuration cable Safety guide

Physical

Colour	Black
Height	179.1 cm
Width	5.5 cm
Depth	4.6 cm
Net Weight	6.52 kg
Mounting Location	Side
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

[In] Rated Current	16 A
--------------------	------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Permissible Voltage	100...120 V
Input Current Limits	20 A
Load Capacity	1920 VA
Network Frequency	50/60 Hz

Output

Number Of Power Socket Outlets	24 NEMA 5-20R
--------------------------------	---------------

Conformance

Product Certifications	cUL listed UL listed
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient Air Temperature For Operation	-5...60 °C
Relative Humidity	5...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage Altitude	0.00...15240.00 m

Packing Units

Package 1 Height	200.6 cm
Package 1 Width	16.47 cm
Package 1 Length	10.83 cm
Package 1 Weight	8.6 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)