

Product data sheet

Specifications



Rack PDU 2G, Switched, 30A, 200/208V, (21) C13 & (3) C19 (BEING DISCONTINUED - SEE APDU9941)

AP8941

! Discontinued - Service only

! Discontinued on: Jun 20, 2022

Overview

| | |
|--------------|--|
| Presentation | APC Switched Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Individual outlet control provides advanced load management. Real-time remote monitoring and user-defined alarms help prevent potential circuit overloads that can cause accidental power loss to critical equipment. Included capabilities include individual remote on/off by outlet, power-on sequencing with time delays, outlet level grouping, and outlet grouping on multiple APC Switched Rack PDUs. Easily access, configure, and manage this metered PDU from remote locations. A network management interface provides standards-based management via Web, SNMP, and Command Line Interface. This Switched PDU from APC provides (21) IEC 60320 C13, (3) IEC 60320 C190 outlets to supply power to rack equipment. User customized alarms and an embedded memory log are included. Volts, amps, real power (kW), and energy (kWh) data is provided to support energy management. An embedded log memory to reports historic metered data. Display details current, power, and voltage measurements and offers local user access. An environmental monitoring port for external temperature/humidity monitoring is available (sensor sold separately model AP9335T or AP9335TH). Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events and breakers are ultra-low profile. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Safety guide, Serial configuration cable. |
|--------------|--|

| | |
|-----------|------------------|
| Lead Time | Usually in Stock |
|-----------|------------------|

Main

| | |
|-----------------------|--|
| Main Input Voltage | 200 V 208 V 230 V |
| Main Output Voltage | 200 V 208 V |
| Input Connection Type | NEMA L6-30P |
| Number Of Rack Unit | 0U |
| Cable Length | 3.05 m |
| Number Of Cables | 1 |
| Provided Equipment | Installation guide Rack mounting brackets Serial configuration cable Safety guide |

Physical

| | |
|--------|----------|
| Colour | Black |
| Height | 182.9 cm |
| Width | 5.6 cm |
| Depth | 4.6 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------|--------------------|
| Net Weight | 7.64 kg |
| Mounting Location | Side |
| Mounting Preference | No preference |
| Mounting Mode | Not rack-mountable |
| Usb Compatible | No |

Input

| | |
|----------------------|----------|
| [In] Rated Current | 24 A |
| Max Line Current | 30 A |
| Input Current Limits | 30 A |
| Load Capacity | 4992 VA |
| Network Frequency | 50/60 Hz |

Output

| | |
|--------------------------------|-------------------------------------|
| Number Of Power Socket Outlets | 21 IEC 60320 C13 3 IEC 60320 C19 |
|--------------------------------|-------------------------------------|

Conformance

| | |
|------------------------|--|
| Product Certifications | cUL listed PSE UL listed VCCI class A |
| Standards | FCC part 15 class A ICES-003 |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient Air Temperature For Operation | -5...60 °C |
| Relative Humidity | 5...95 % |
| Operating Altitude | 0...10000 ft |
| Ambient Air Temperature For Storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage Altitude | 0.00...15240.00 m |

Packing Units

| | |
|------------------------------|---------|
| Package 1 Height | 204 cm |
| Package 1 Width | 16.5 cm |
| Package 1 Length | 12.4 cm |
| Package 1 Weight | 10 kg |
| Number Of Units In Package 3 | 48 |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions