

Product data sheet

Specifications



MasterSwitch VM, Zero U, 16A, 208&230V, (8)C13

AP9229

 **Discontinued on:** Jun 14, 2022

 **Discontinued**

Overview

Lead Time Usually in Stock

Main

Colour	Beige
Cord Length	2.50 m
Number Of Cables	1
Provided Equipment	10 ft RJ11 cable CD with software Rack mounting brackets User manual

Complementary

Input Voltage	120 V 208 V 230 V
Height	118.1 cm
Width	4.4 cm
Output Voltage	120 V 208 V 230 V
Depth	4.4 cm
Net Weight	3.18 kg
Mounting Preference	No preference
Input Plug Type	IEC 60320 C20
Mounting Mode	Not rack-mountable
Rack Units	0U
Mounting Position	Vertical
Permissible Voltage	90...250 V
Max Line Current	16 A
Input Current Limits	16 A
Load Capacity	3328 VA
Network Frequency	50/60 Hz
Outlet Type And Quantity	8 IEC 60320 C13

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product Certifications	C-Tick CSA DOC/Industry Canada UL recognized VCCI VDE
Standards	EN 55022 class A EN 55024 FCC part 15 class A UL 1950
Ambient Air Temperature For Operation	0...45 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...65 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	132.7 cm
Package 1 Width	8.3 cm
Package 1 Length	17.1 cm
Package 1 Weight	3.632 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------