

Product data sheet

Characteristics

AP9559

Rack PDU, Basic, 1U, 16A, 208&230V, (10)C13 & (2)C19



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cable length	8.2 Ft (2.5 m)
Number of cables	1
Provided Equipment	User Manual Rack Mounting brackets

Complementary

Main Input Voltage	120 V 208 V 230 V
Height	1.7 In (4.4 cm)
Width	17.6 In (44.7 cm)
Output voltage	120 V 208 V 230 V
Depth	2.2 In (5.7 cm)
Net Weight	2.16 Lb(US) (0.98 kg)
Mounting location	Front Rear
Mounting preference	No preference
Input Connection Type	IEC 60320 C20
Mounting Mode	Rack-mounted
Number of rack unit	1U
Mounting position	Horizontal
Acceptable Input Voltage	90...250 V
Max line current	16 A
Input current limits	16 A

Load Capacity	3680 VA
Input Frequency	50/60 Hz
Number of power socket outlets	10 IEC 60320 C13 2 IEC 60320 C19

Environment

Product Certifications	cUL Listed[RETURN]CE[RETURN]JUL Listed[RETURN]VDE[RETURN]Victoria
Ambient Air Temperature for Operation	32.0000000000...113.0000000000 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13.0000000000...149.0000000000 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 Ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304123521
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 In (16.5 cm)
Package 1 Width	19.02 In (48.3 cm)
Package 1 Length	6.0 In (15.2 cm)
Package 1 Weight	5.192 Lb(US) (2.355 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**