

Product data sheet

Specifications

Rack PDU, Basic, 1U, 30A, 208V, (12) C13



AP9571

 **Discontinued on:** Jun 14, 2022

 **Discontinued**

Overview

Lead time Usually in Stock

Main

Colour	Black
product or component type	PDU
PDU type	Basic
Cord length	3.7 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets User manual

Complementary

Input Voltage	208 V
Height	4.3 cm
Width	44.5 cm
Output Voltage	208 V
Depth	6.4 cm
net weight	2.55 kg
mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
[In] rated current	24 A
Permissible voltage	200...240 V
Max line current	30 A
Input current limits	30 A
Load capacity	4992 VA
Number of power socket outlets	12

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Network frequency	50/60 Hz
Outlet type and quantity	12 IEC 60320 C13

Environment

Product certifications	cUL listed UL listed
Standards	UL 60950
Ambient air temperature for operation	-15...45 °C
Relative humidity	5...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	48.6 cm
Package 1 Length	17.7 cm
Package 1 Weight	3.632 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------