Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Rack PDU, Basic, 1U, 30A, 208V, (10) C13



AP9571A

Overview

| Presentation | Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (10) C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment. |
|--------------|--|
| Lead time | Usually in Stock |

Main

| Colour | Black |
|---------------------------|---|
| product or component type | PDU |
| PDU type | Basic |
| Cord length | 3.7 m |
| Number of cables | 1 |
| provided equipment | Installation guide Rack mounting brackets User manual |

Complementary

| Input Voltage | 200 V 208 V 230 V | |
|---------------------|-------------------------|--|
| Height | 4.4 cm | |
| Width | 44.5 cm | |
| Output Voltage | 208 V | |
| Depth | 7.7 cm | |
| net weight | 2.55 kg | |
| mounting location | Front Rear | |
| Mounting preference | No preference | |
| Input Plug Type | NEMA L6-30P | |
| mounting mode | Rack-mounted | |
| Rack units | 1U | |
| Mounting position | Horizontal | |
| [In] rated current | 24 A | |
| Permissible voltage | 200240 V | |
| Max line current | 30 A | |

| Input current limits | 30 A |
|--------------------------|------------------|
| Load capacity | 4992 VA |
| Network frequency | 50/60 Hz |
| Outlet type and quantity | 10 IEC 60320 C13 |

Environment

| Product certifications | cUL listed PSE UL listed |
|---------------------------------------|--------------------------------|
| Standards | UL 60950 |
| Ambient air temperature for operation | -545 °C |
| Relative humidity | 595 % |
| Operating altitude | 015000 ft |
| Ambient air temperature for storage | -2565 °C |
| Storage Relative Humidity | 595 % |
| Storage altitude | 0.00000000015240.000000000 m |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.1 cm |
| Package 1 Width | 17.4 cm |
| Package 1 Length | 48.3 cm |
| Package 1 Weight | 3.64 kg |

Contractual warranty

Warranty 2 years repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product



Take-Back Program Available

Well-being performance

Lead Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |