


Product data sheet

Specifications



APC Back-UPS 650VA Standby with Schuko

BC650-RS

 **Discontinued on:** Jun 14, 2022

 **Discontinued**




Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	390 W
Rated Power In Va	650 VA
Input Connection Type	Schuko CEE 7/7P
Output Connection Type	3 Schuko CEE 7 1 Schuko CEE 7 surge
Cable Length	1.16 m
Battery Type	Lead-acid battery
Provided Equipment	CD with software User manual USB cable

Batteries & Runtime

Run Time	View Runtime Graph 
Efficiency	View Efficiency Graph 
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	10 W rated
Battery Power In Vah	84 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	APCRBC110 
Extended Runtime	0

General

Product Web Sub-Family	Entry level
Number Of Power Module Free Slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Black
Height	20 cm
Width	11.5 cm
Depth	25.6 cm
Net Weight	5.8 kg
Mounting Support	Desktop
Mounting Preference	No preference
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes

Input

Network Frequency	50/60 Hz
Input Voltage Limits	160...278 V adjustable 180...266 V
Maximum Input Current	3 A
Switching Current Capacity	7 A

Output

Maximum Configurable Power In W	390 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Standby
Wave Type	Stepped approximation to a sinewave
Maximum Output Current	7 A
Maximum Configurable Power In Va	650 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	EAC
------------------------	-----

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...9144.00 m
Acoustic Level	45 dBA

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control Panel	LED Status display with on line : on battery

Surge Protection and Filtering

Surge Energy Rate	273 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	34.35 cm
Package 1 Width	20 cm
Package 1 Length	27.85 cm
Package 1 Weight	6.586 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)