

Product data sheet

Specifications



APC Back-UPS 650VA, 230V, 4 Schuko CEE 7 outlets

BC650-RSX761

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	360 W
Rated Power In Va	650 VA
Input Connection Type	Schuko CEE 7/7P
Nb Of Power Socket Outlets	4 Schuko CEE 7
Cable Length	1.00 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Battery Charger Power	15 W rated
Battery Power In Vah	124 VAh runtime
Battery Life	2...4 year(s)
Replacement Battery	RBC17
Extended Runtime	0

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Height	20 cm
--------	-------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	11.5 cm
Depth	25.6 cm
Net Weight	5.5 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz
Input Voltage Limits	180...266 V
Input Current	7 A (1 phase)

Output

Maximum Configurable Power In W	360 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Standby
Wave Type	Stepped approximation to a sinewave
Efficiency	96.2 % (full load)
Maximum Configurable Power In Va	650 VA
Transfer Time	8 ms typical : 10 ms maximum

Conformance

Product Certifications	EAC
------------------------	-----

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage Altitude	0.00...9144.00 m
Acoustic Level	45 dBA

Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	273 J
-------------------	-------

Packing Units

Package 1 Height	28.7 cm
Package 1 Width	45 cm
Package 1 Length	22.1 cm
Package 1 Weight	6.15 kg
Number Of Units In Package 3	60
Package 3 Height	113.54 cm
Package 3 Width	61.47 cm
Package 3 Length	76.96 cm
Package 3 Weight	377.03 kg
Scs14	10731304326318
Pallet Unit Layers	12
Pallet Layers	5

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ RoHS Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant
[EU RoHS Declaration](#)