

Product data sheet

Specifications



APC Back-UPS ES 525VA Universal for ASE

BE525-AS

 **Discontinued on:** Jun 14, 2022

 **Discontinued**



Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	315 W
Rated Power In Va	525 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	3 universal receptacle 1 universal receptacle surge
Number Of Rack Unit	0U
Cable Length	1.98 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software 1 x detachable 2.0 m NEMA 5-15P to IEC C13 power cord Telephone cable User manual Warranty card

Batteries & Runtime

Run Time	View Runtime Graph 
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	10 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	9 W rated
Battery Power In Vah	86 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	RBC2 
Extended Runtime	0

General

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Max Runtime	22 min
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Charcoal
Height	8.5 cm
Width	29.8 cm
Depth	18.3 cm
Net Weight	3.64 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50 Hz +/- 3 Hz
Input Voltage Limits	180...260 V

Output

Maximum Configurable Power In W	315 W
Ups Type	Standby
Maximum Output Current	230 A
Maximum Configurable Power In Va	525 VA

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-5...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA
Heat Dissipation	31 Btu/h

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control Panel	LED Status display with on line : on battery

Surge Protection and Filtering

Surge Energy Rate	450 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.8 cm
Package 1 Width	33.5 cm
Package 1 Length	22.7 cm
Package 1 Weight	4.191 kg
Scc14	10731304191619

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)