

Home

Products

Support

Services

Selectors

How to Buy

Back-UPS ES

APC Back-UPS ES 550VA 230V Italian



+

More Images

APC Back-UPS ES, 330 Watts / 550 VA,Input 230V / Output 230V

Includes:

USB cable, User Manual, Wall -mounting template

Standard Lead Time

: Usually in Stock

Runtime Chart

BE550-IT

Add Options

Email Technical Specifications

Printer Friendly

Technical Specifications

Product Overview

Documentation

Software & Firmware

Options

Compare Models

Output

Output Power Capacity	330 Watts / 550 VA
Max Configurable Power	330 Watts / 550 VA
Nominal Output Voltage	230V
Output Connections	(4) Schuko CEE 7 (Battery Backup) (4) Schuko CEE 7 (Surge Protection)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	Italian CEI 23-16
Cord Length	1.83 meters
Maximum Input Current	10A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
Replacement Battery	RBC2 , RBC2J
RBC™ Quantity	1
Typical Backup Time at Half Load	14.0 minutes (165 Watts)
Typical Backup Time at Full Load	3.4 minutes (330 Watts)
Runtime Chart	Back-UPS ES

Communications & Management

Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	310 Joules
Filtering	Full time multi -pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Dataline protection	RJ-45 Modem/Fax/DSL/10-100 Base-T protection

Physical

Maximum Height	86.00 mm
Maximum Width	230.00 mm
Maximum depth	285.00 mm
Net Weight	6.40 KG
Shipping Weight	6.90 KG
Shipping Height	132.00 mm
Shipping Width	300.00 mm
Shipping Depth	366.00 mm
Master Carton Units	2.00
Master Carton Weight	14.20 KG
Color	Charcoal
SCC Codes	1073130423341 8
Units per Pallet	72.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-15000 meters
Storage Temperature	0 - 40 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA

Conformance

Regulatory Approvals	CE
Standard Warranty	3 years repair or replace

**The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.

Copyright © American Power Conversion Corp., all rights reserved

About APC

Investors

Job Seekers

Press

Feedback

Contact

Privacy Policy