Back-UPS ES

APC BACK-UPS ES 600VA LATIN AMERICA 120V

BE600-LM

Add Options

More Images

APC Back-UPS ES, 360 Watts / 600 VA,Input 120V / Output 120V, Interface Port USB

Includes: CD with software, USB cable, User Manual

Standard Lead Time : Usually in Stock

Runtime Chart

Email Technical Specifications

Printer Friendly

Technical Specifications | Product Overview | Documentation | Software & Firmware | Options | Compare Models

Output

Output Power Capacity	360 Watts / 600 VA
Max Configurable Power	360 Watts / 600 VA
Nominal Output Voltage	120V
Output Connections	(6) Brazilian 2P+T (Battery Backup)

Input

Nominal Input Voltage	120V
Input Frequency	60 Hz +/- 3 Hz
Input Connections	NEMA 5-15P
Cord Length	1.83 meters
Input voltage range for main operations	94 - 140V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
Replacement Battery	RBC2, RBC2J
RBC™ Quantity	1
Typical Backup Time at Half Load	10.1 minutes (180 Watts)
Typical Backup Time at Full Load	2.1 minutes (360 Watts)
Runtime Chart	Back-UPS ES

Communications & Management

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	450 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Dataline protection	RJ-11 Modem/Fax protection (two wire single line)

Physical

Maximum Height	102.00 mm
Maximum Width	280.00 mm
Maximum depth	187.00 mm
Net Weight	7.36 KG
Shipping Weight	8.00 KG
Shipping Height	191.00 mm
Shipping Width	353.00 mm
Shipping Depth	257.00 mm
Master Carton Units	2.00
Master Carton Weight	14.00 KG
Color	Charcoal
SCC Codes	1073130421422 6
Units per Pallet	60.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	0 - 40 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-3000 meters
Audible noise at 1 meter from surface of unit	40.00 dBA

Conformance

Regulatory Approvals	NOM
Standard Warranty	2 years repair or replace

**The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.

Copyright © American Power Conversion Corp., all rights reserved